


GEM chambers for SoLID

Nilanga Liyanage

University of Virginia

Tracking needs for SoLID (PVDIS)

- Rate: from 100 kHz to 600 kHz (with baffles), GEANT3 estimation
- Spatial Resolution: ~ 0.2 mm (σ)
- Total area: 23 m² total area (30 sectors x 4 planes, each sector cover 10 degree)
- Need to be Magnetic field tolerant



Lumi = $5.4E^{38}$ /cm²/s

Choice of the technology

System Requirements	Tracking Technology		
	Drift	MPGD	Silicon
High Rate (up to): 1 MHz/cm²	NO	MHz/mm²	MHz/mm²
Resolution: 200 μm	Achievable	50 μm	30 μm
Large Area: Single chamber up to 0.5 m ² total 23 m ²	YES	Doable	Very Expensive


Flexibility in readout geometry and lower spark rate

GEM

μMs

New recent development in resistive μM and GEM + μM to improve spark rate


GEM working principle



Recent technology: F. Sauli, Nucl. Instrum. Methods A386(1997)531

COMPASS GEM Tracker



- A tracker of twenty two 31 cm x 31 cm GEM chambers successfully operated for years
- Rates as high as 2.5 MHz/cm²



COMPASS readout plane (31x31 cm²)

70 μm resolution achieved by strips centroid

⇒ **Analog readout required (used the APV25 chip)**




GEM Rate capability

- Multiplication stages shielded from each other: much reduced feed back
- Slow moving positive ions localized to holes, away from the induction region
- Most of the created electrons contribute to signal: can operate at low gains

Much higher rates compared to wire chambers: $\sim 50 \text{ MHz/cm}^2$

Maximum rate expected for SoLID GEM trackers




Triple GEM
Poli Lener, PhD Thesis - Rome 2005

PVDIS GEM configuration




- Current proposal to instrument locations 5, 6, 7, and 8 with GEM:
- 30 GEM modules at each location: each module with a 10-degree angular width.

Plane	Z (cm)	R_I (cm)	R_O (cm)	Active area (m ²)
5	150	55	115	2.7
6	190	65	140	4.0
7	290	105	200	7.6
8	310	115	215	8.6
total:				~ 23







Largest GEM module size required: 100 cm x (20-38) cm

PVDIS GEM configuration




SIDIS GEM configuration



PVDIS GEM configuration

- Suggested readout scheme:
 - a 2D readout optimized to get high accuracy in the ϕ coordinate, lower but sufficient resolution in the r coordinate.
 - each set of stripes parallel to one of the radial sides of the module: i.e. stripes at a 10-deg stereo angle to each other.
 - strip pitch is 0.6 mm for locations 7 and 8;
 - 0.4 mm for locations 5 and 6.
 - Issues:
 - High capacitance in long readout strips; will signal to noise ratio be an issue ?
 - How well will the 10-deg stereo angle separated strip layers work ? - need to test with prototypes.



PVDIS GEM configuration

- For this readout scheme readout channel estimation

Plane	Z (cm)	R_I (cm)	R_O (cm)	# of channels
5	150	55	115	30 k
6	190	65	140	36 k
7	290	105	200	35 k
8	310	115	215	38 k
total:				140 k


- with 20% spares, we will need about 170 k channels.
- **Good news:** cost of electronics going down - cost per channel for the RD51 SRS APV-25 based readout is estimated to be ~ \$ 2.50 - \$ 3.00 + R&D expenses to optimize electronics for SoLID needs.

The total cost of readout electronics can be less than \$ 1 M

SIDIS GEM configuration

- Six locations instrumented with GEM:
- PVDIS GEM modules can be re-arranged to make all chamber layers for SIDIS. - move the PVDIS modules closer to the axis so that they are next to each other

Plane	Z (cm)	R_I (cm)	R_O (cm)	Active area	# of channels
1	197	46	76	1.1	24 k
2	250	28	93	2.5	30 k
3	290	31	107	3.3	33 k
4	352	39	135	5.2	28 k
5	435	49	95	2.1	20 k
6	592	67	127	3.7	26 k
total:				~18	~ 161 k



- More than enough electronic channels from PVDIS setup.
- The two configurations will work well with no need for new GEM or electronics fabrication.

large area GEM chamber challenges

- SoLID needs GEM modules as large as 100 cm x 40 cm.
- The biggest challenge used to be the non-availability of large area GEM foils.
- **Not a problem anymore:** CERN shop can make foils as large as 200 cm x 50 cm now.
- One problem may be the production capacity of the CERN shop: especially if a LHC related large GEM project gets underway.
- Currently work going on to develop large GEM production capabilities in China.

Major recent development at CERN PCB shop towards large GEM foils

- Base material only ~ 45 cm wide roll.
- Used a double mask technique for etching: hard to the two masks accurately: **Max area limited to ~ 45 cm x 45 cm previously.**




Double Mask



Bias top surface to - w.r.t chemical bath



Single Mask



Single Mask technique allows to make GEM foils as large as 200 cm x 50 cm

Major recent development towards large GEM foils

- Splicing GEM foils together: seam is only 2 mm wide
- Performance of the rest of the GEM foil unaffected




Industrial Production of GEMs


- Many anticipated users of GEMs in the near future; CERN shop can't keep up.
- Several Industrial production around the world starting with CERN technology transfer:
 - TechEtch, Plymouth, MA, USA : GEM foils up to ~ 40 cm; produced all foils for STAR FGT.
 - NewFlex Technology, South Korea: produced the tested foils up to 10 x 10 cm²; plans for large production up to 1 m foils.
 - TechTra in Poland
 - India
 - China
 - ...




CERN GEM, single mask technology



Korean GEM, double mask technology




Large GEM chamber projects



FGT 2D readout board (r-φ)


FGT quarter section
($r_{\min} = 10.5 \text{ cm}$,
 $r_{\max} = 39 \text{ cm}$)



Large prototype GEM module for CMS: 99 cm x (22 - 45.5) cm

STAR Forward GEM Tracker


- 6 triple-GEM disks around beam
- IR ~ 10.5 cm, OR ~ 39 cm
- APV25 electronics



TOTEM T1 prototype made with single mask GEM foils (33 cm x 66 cm)

CMS prototype similar to the dimensions of largest SOLID chambers



CMS high-eta GEM tracker proposal




GEMs for triggering and tracking

- Proposal to cover the $1.6 < |\eta| < 2.4$ region with GEMs.
- GEMs for
- 240 GEM chambers


Total active area covered $\sim 300 \text{ m}^2$



CMS large area prototype GEM construction




Large prototype GEM module for CMS:
99 cm x (22 - 45.5) cm




Two full size prototypes already constructed and tested.

- 1D readout
- Different GEM gaps to optimize timing (3/2/2/2 mm and (3/1/2/1 mm)
- Single mask.
- Also 5 small prototypes.



Jefferson Lab SBS Trackers - Front Tracker




- ❑ 50 cm x 40 cm Modules are assembled to form larger chambers with different sizes
- ❑ Front tracker: Six 40 cm x 150 cm GEM layers
 - ❑ INFN Funding: to be built in Italy
- ❑ Polarimeter trackers: Eight 50 cm x 200 cm GEM layers
 - ❑ to be built in Virginia
- ❑ Total GEM coverage of SBS ~ 16 m²

76 modules
In Virginia


SBS GEM module construction currently going on in Italy and at UVA

The currently ongoing GEM chamber work



New 40 cm x 50 cm GEM stretcher at Uva

Stretching time $\sim 1 - 2$ hours
Foil Tension: $T \sim 0.5$ kg/cm




Fully equipped INFN prototype 40x50 cm² GEM module for a beam test at DESY

- A 100 cm x (25-40) cm prototype GEM module with 2D readout is currently under design at Uva. (EIC detector R&D effort)
- Expect to construct and test this chamber this Fall - Can learn a great deal for SoLID GEMs from this:
 - develop techniques for fabrication of large GEM modules.
 - study readout schemes: 10 degree stereo angle
 - Study issues of signal to noise ratio for long readout strips.

GEM chamber electronics




- The RD-51 Scalable Readout System provides a low-cost, common platform that can accommodate different readout chips.
- Currently tested with APV25-S1 chip.
- Drawback with the APV25 chip: may not be fast enough for SoLID
- Need to work on finding a suitable chip for SoLID readout and incorporating it into SRS (?)



SRS system has the benefit of the large team effort backed by RD-51

RD-51 plans to commercialize the fabrication; there will be the possibility to get very large systems in the future.

- Uva group now owns an APV25 system (2000 chan.) from the RD-51 Scalable Readout System (SRS) development.



SoLID GEM chamber Collaboration

- University of Science and Technology of China (USTC)
- Tsinghua University
- Lanzhou University
- China Institute of Atomic Energy (CIAE)
- Institute of Modern physics
- INFN-Rome
- University of Virginia

rough cost estimate

Item	Quantity	Unit cost	Total cost	Material only unit cost	Material only total cost
GEM foil	~100 m ²	\$2000/m ²	0.2 M	\$3000/m ²	0.2 M
readout boards	120	\$ 2500	0.3 M	\$ 2500	0.3 M
chamber support frame	120	\$ 1500	0.2 M	\$ 1500	0.2 M
Supplies and tooling			0.1 M		0.1 M
FEE and DAQ	200 k	\$ 5.0	1.0 M	\$ 3.0	0.6 M
cables, power, etc			0.5 M		0.5 M
Gas system			0.1 M		0.1 M
Labor: Technicians	6 FTE-years	\$ 100 k	0.6 M		-
Labor: Grad students	6 student-years	\$ 50 k	0.3 M		-
support structure and integration			???		???
TOTAL:			~ 3.3 M		~ 2.0 M
With 33% contingency			~4.4 M		~2.7 M

R&D and prototyping expenses: ~ \$ 300 k

Bottom-line

- With the strong effort led by RD-51 towards large GEM chambers and readout electronics:
 - Costs are coming down
 - Many technical challenges are overcome
 - But SoLID is a very large and very complicated GEM project from any standard; no one has ever done anything even close to this size.
 - We are now starting on SBS GEM construction, this is about 70% of the size of the SoLID GEM project.
 - So with:
 - large GEM chamber construction for SBS in Rome and at UvA
 - the infrastructure and expertise we gain from large GEM prototyping at UvA, and
 - Expertise gained by our Chinese collaborators.
- we will be ready for the SoLID GEM construction in a couple of years.