
## Cable Path



Cable type	#	Length	Explain
Series	1 1 1 1 14 1 1	S2C S2C T2S T2S Short Short S2L S2L S2L	75ohm video cable Patch cable 25D Male to Female Airflow meter (Shielded 4 conductor cable 22AWG) Patch cable 25D Male to Female RTD readout / 15DB (RS 485) USB Airflow RS232 Oven temp RS232 Heater temp RS232
BNC RG58	9 1 10 26	C2U C2T T2U Short	4 NMR + 3 PNMR + 2 EPR 1 NMR RF 8 NMR + 1 EPR +1 pNMR
RTD	10 12	T2L Short	Oven & Cell (Shielded 4 conductor cable 22AWG) Shielded 4 conductor wire 22 awg10 RTD
Thermocouple	1	T2S	
Power Cable	2 4 2	T2L T2L T2S	twisted 2 conductor cable 10 AWG twisted 2 conductor cable 16 AWG twisted 2 conductor cable 12 AWG
GPIB	14	Short	
2 wire Interlock Connection	1 1 1 2	L2LR S2L OA2L Short	

## Cable Count

: Cables from outside to Hall C

C2U: Counting House to Under Target

C2T: Counting House to Target

T2U: Target to Under Target

OA2LR: Optical Area to Laser Room

T2L: Target to Large Shield T2S: Target to Small Shield

Short: 6~9 feet?