

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 10014

DESCRIPTION: 1 WELDING CABLE

CONSTRUCTION: This cable consists of one bare copper conductor with integral insulation and jacket.

APPROVALS: MSHA

APPLICATION: Welding Cable Applications

Construction Parame	eters:
----------------------------	--------

Conductor 1 AWG Bare Copper

Stranding 7x114/.0098

Insulation Material TPE

Insulation Thickness 0.073" Nom. Insulated Conductor Diameter 0.476" Nom.

Number of Conductors 1

Approximate Cable Weight 298.6 Lbs/1M' Nom.

Electrical Properties:

Temperature Rating -50°C to 105°C Operating Voltage 600V Max
DC Resistance per Conductor @ 20°C 0.13 Ohms/1M'
Ampacity 150 Amps

Insulation Color Black

Legend (Surface Ink Print) COLEMAN CABLE & WIRE CO. 1 AWG 600 VOLT WELDING

CABLE 105C P-241-3-MSHA MADE IN USA

This product complies with European Directive 2002/95/EC (RoHS)

On special orders, the customer will accept all mil lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name	Date Signed
Customer Approval	

Specification Issue Date: July 30, 2010