

1-800-383-7323 US/CAN www.energizer.com

ΑΑΑ

ENERGIZER NO. L92



Industry Standard Dimensions mm (inches) This Battery has Underwriters Liberatories component Recognition 10.50 (0.413) 9.50 (0.374) 0.84 (0.033)Minimum (+) 44.50 (1.752)43.30 (1.705)

(-)

Constant Power Performance

4.30 (0.169) Minimum Classification: "Cylindrical Lithium" Chemical System: Lithium/Iron Disulfide (Li/FeS₂) Designation: ANSI 24-LF, IEC-FR03 Nominal Voltage: 1.5 Volts Storage Temp: -40°C to 60°C (-40°F to 140°F) -40°C to 60°C (-40°F to 140°F) **Operating Temp:** 1,250 mAh* (to 1.0 volts) Typical Capacity: Capacity Test: 100 mA continuous drain (21°C) * Varies according to the applied load, temperature, and cutoff voltage. **Typical Weight:** 7.6 grams (0.3 oz.) **Typical Volume:** 3.8 cubic centimeters (0.2 cubic inch) Max Discharge: 1.5 Amps Continuous 2.0 Amps Pulse (2 sec on/8 sec off) Typical Li Content: 0.5 grams (0.02 oz.) UL Listed: MH29980 Shelf Life: 15 years at 21°C (90% of rated capacity) Shipping: For complete details, please reference: Global (except US): Special Provision A45 of the International Air Transport Association Dangerous **Goods Regulations** United States: 49 CFR 173.185

Specifications

Storage/Capacity Characteristics

Effects of Storage at Various Temperatures



Constant Current Performance



Important Notice

This data sheet contains typical information specific to batteries manufactured at the time of its publication. **Contents herein do not constitute a warranty.** ©Energizer - All Rights Reserved PRODUCT DATASHEET



1-800-383-7323 US/CAN www.energizer.com

250 mA (21°C)

Constant Current Performance

Typical Discharge Characteristics (21°C / 0°C / -20°C)

3

Service (hours)

4

5

6

ENERGIZER NO. L92

1.6

1.5

1.4

1.3

1.2

1.1

1.0

0.9

0.8

0

250 mA (-20°C)

1

250 mA (0°C)

2

Voltage (CCV)



Industry Standard Tests (21°C)



This data sheet contains typical information specific to batteries manufactured at the time of its publication. **Contents herein do not constitute a warranty.** ©Energizer - All Rights Reserved

Form No. EBC - 42091