

RoHS Compliant

[USOC Color Code]



Performance:

Meets Cat.3 EIA/TIA Standard.

Materials :

RJ-12 Jack : BK Color : PC / Others Color : Fireproof-ABS

6P6C 6 micro inches gold plating

Inside Plastic Body : Fireproof ABS

IDC Pin : Bronze & Nickel Plated

Cap : PC

Label Color Code : USOC

IDC Description : For 22-26 AWG.

Electrical Specifications:

Insulation Resistance : 500M ohms (min.)

Contact Resistance : 20m ohms (max.)

Current Rating : 1.5 Amps .


DC Resistance : 0.1 ohm (max.)

Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

Mechanical Specifications:

RJ-12 Jack Insertion Cycle : Over 1000 Cycles (min.)

Operation Temperature : -40 ~ +70 degree / C



DCC. NO.
A4 DRAWING NO.

MATERIAL		GOLDSUN ELECTRONICS CO., LTD.			
		JAMECO NO.	GOLDSUN NO.		
		213517	KT3-L201X-ROHS		
DRAWN: Kiki Chen		Description	Rev.		
VERIFY PEOPLE: Ada Zheng , Ivy Lan		CAT.3 KEYSTONE JACK 6P6C WHITE	1		
		UNIT: mm	SCALE:	SHEET 1 OF 1	CAS No: ERN No: