


# PIN RECEPTACLES

FOR .015" - .025" DIAMETER PINS

## 0660

0660-0-15-XX-30-XX-10-0


Solder mount in .051 min. mounting hole



## 0677

0677-0-15-XX-30-XX-10-0


Solder mount in .051 min. mounting hole



## 0555

0555-0-15-XX-32-XX-10-0


Solder mount in .053 min. mounting hole  
Also available on 16mm wide carrier tape:  
1,800 parts per 13" reel  
Order as: 0555-0-57-XX-32-XX-10-0



## 0558

0558-0-15-XX-30-XX-10-0


Solder mount in .061 min. mounting hole



## 0675/0679

067X-0-15-XX-30-XX-10-0

Solder mount in .054 min. mounting hole




| Basic Part Number | Length L |
|-------------------|----------|
| 0675-0            | .145     |
| 0679-0            | .203     |

## 1065/1066/7065

X06X-0-15-XX-30-XX-10-0

Solder mount in .055 min. mounting hole




| Basic Part Number | Length L |
|-------------------|----------|
| 1065-0            | .190     |
| 1066-0            | .160     |
| 7065-0            | .181     |

## 0682

0682-0-15-XX-32-XX-10-0


Solder mount in .056 min. mounting hole  
Also available on 16mm wide carrier tape:  
1,500 parts per 13" reel  
Order as: 0682-0-57-XX-32-XX-10-0



## 0667

0667-0-15-XX-30-XX-10-0


Solder mount in .057 min. mounting hole  
Also available on 16mm wide carrier tape:  
1,700 parts per 13" reel  
Order as: 0667-0-57-XX-30-XX-10-0



## 0665

0665-0-15-XX-30-XX-10-0


Solder mount in .061 min. mounting hole



## 4286

4286-0-15-XX-30-XX-10-0

Hex press-fit in .055 plated through-hole



### SPECIFICATIONS:

**Shell Material:** Brass Alloy 360, 1/2 Hard

**Contact Material:** Beryllium Copper Alloy 172, HT

**Dimensions:** Inches

**Tolerances On:** Lengths:  $\pm .005$

Diameters:  $\pm .002$

Angles:  $\pm 2^\circ$



ORDER CODE: XXXX - X - 15 - XX - XX - XX - 10 - 0

BASIC PART #

SPECIFY SHELL FINISH:

01 200  $\mu$ " TIN/LEAD OVER NICKEL

◆ 80 200  $\mu$ " TIN OVER NICKEL (RoHS)

◆ 15 10  $\mu$ " GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

02 100  $\mu$ " TIN/LEAD OVER NICKEL

◆ 84 100  $\mu$ " TIN OVER NICKEL (RoHS)

◆ 27 30  $\mu$ " GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#30 or #32 CONTACT (DATA ON PAGE 253)

(For alternate contact choices, see groups B and C on page 248)



Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com