



## Product Information

# No-Clean Flux Remover

No-Clean Defluxer  
1660

## Introduction

No-Clean Flux Remover 1660 is a non-flammable, rapidly evaporating blended AK225 designed specifically for the removal of No-Clean Flux and white residue. No-Clean Flux Remover also effectively and aggressively removes greases, oils and similar soils from contacts, PCBs, connectors, motors, generators, and relays.

### Features / Benefits

Removes White Residue  
Non-Flammable  
Rapidly Evaporating  
Zero Residue  
Non-Corrosive

### Physical Properties

Boiling Point	40°C / 104°F
Flash Point (TCC)	None
Evaporation Rate	>1
Surface Tension	
Kauri-Butanol (KB Value)	

## Chemical Components

3,3-Dichloro-1,1,1,2,2-pentafluoropropane...	(422-56-0)	20-30%
1,3-Dichloro-1,1,2,2,3-pentafluoropropane...	(507-55-1)	25-30%
Trans-dichloroethylene.....	(156-60-5)	22-29%
Methanol.....	(67-56-1)	4.8%
Nitromethane.....	(75-52-5)	< .5%
1,1,1,2-tetrafluoroethane.....	(811-97-2)	18-23%
Carbon Dioxide.....	(124-38-9)	1-2%

## Plastic Compatibility

Material	Compatibility	Material	Compatibility
ABS	Not Compatible	PMMA	Not Compatible
Nylon	Excellent	POM	Excellent
Lexan	Not Compatible	PP	Excellent
HDPE	Excellent	PS	Not Compatible
CDPE	Excellent	PTFE	Excellent
C. E. Phenolic	Excellent	PVC	Excellent

## Environmental Policy

---

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

## Packaging and Availability

---

No-Clean Flux Remover may be ordered in the following container sizes:

1660-6S	6 Ounce Aerosol (with Brush Attachment 1995)
1660-12S	12 Ounce Aerosol

## Resources

---

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email [tsales@techspray.com](mailto:tsales@techspray.com) or visit our web site at: [www.techspray.com](http://www.techspray.com).

### North America

Tech Spray L.P.  
P.O. Box 949  
Amarillo, TX 79105  
800-858-4043  
email: [tsales@techspray.com](mailto:tsales@techspray.com)

### Europe

Techspray International  
UNIT 4, 44/46 Bunyan Road, Kempston  
Bedford MK42 8HL United Kingdom  
+44 (0) 1234 855443  
email: [tseurope@techspray.com](mailto:tseurope@techspray.com)

### Countries Outside US

Call to locate a distributor  
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P.  
P.O. Box 949  
Amarillo, TX 79105  
[www.techspray.com](http://www.techspray.com)

