

Replace any food waste disposer with a high speed Whirlaway Apartment Replacement Disposer. Our unique mount system allows installation without replacing the sink flange, saving time and money!


Our exclusive Adapter Collar saves 15 minutes or more on installation. Choose a reliable Whirlaway 1/3 Horsepower

191AP or 1/2 Horsepower 291AP, either one is the perfect choice for any Property Manager. New splash guards is included.

Our "Vortex Powered", permanent magnet motor outperforms the competition, and this powerful yet compact disposer is a real space saver where space is at a premium.

(S Whirlawa)

- **Adapter Allows Mounting** to Any Sink Flange
- **New Splash Guard Included**
- **Stainless Steel, Anti-Jam Swivel Impellers**
- **Corrosion-Proof Grind Chamber and Drain** Housing
- **Fast & Easy Mount System**



Save







4240 E. La Palma Avenue • Anaheim. CA 92807 • 1-800-854-3229

OVER

ELLI

COUNTER

REPLACEMENT

S Whirlaws



WAW-1374



MODEL 191AP & 191AP-PC* • 1/3 H.P. MODEL 291AP & 291AP-PC* • 1/2 H.P.


- Space saving compact design!
- Vortex Powered, permanent magnet motor produces more power per pound.
- Corrosion resistant grinding components.
- Fast & Easy Mount System provides for quick installation.
- New splash guard is included.
- Safe for properly sized septic tanks.
- Longest warranties in the industry demonstrates commitment to quality.

Two Year Over-the-Counter Replacement Warranty (see below).



DIMENSIONS

Knock-out for dishwasher drain connector sized for 7/8" I.D. rubber hose.



Whirlaway[®] Warranty

Any Whirlaway[®] Model 191AP, 191AP-PC, 291AP or 291AP-PC less than two years old that develops a material or mechanical defect will be replaced with a new like model free of charge.

SPECIFICATIONS

S Whiris

	191AP/191AP-PC	291AP/291AP-PC
Motor Horsepower	1/3 H.P.	1/2 H.P.
Motor Speed R.P.M.	1900	2600
Voltage	115	115
Hz	60	60
Current-Amps	4.0	4.0
Motor Type	Permanent Magnet	Permanent Magnet
Sink Flange	Stainless Steel & Celcon	Stainless Steel & Celcon
Stopper	Positive Seal	Positive Seal
Splash Guard	Removable	Removable
Waste Elbow	ABS	ABS
Feed	Continuous	Continuous
Grind Ring	Heavy Gauge Steel	Heavy Gauge Steel
Swivel Impellers	Stainless Steel	Stainless Steel
Turntable	Galvanized Steel	Galvanized Steel
Hopper	Glass Filled Nylon	Glass Filled Nylon
Grinding Chamber	Corrosion Proof Glass Filled	Corrosion Proof Glass Filled
	Polyester	Polyester
Bearings	Permanently Lubricated; Sleeve Type	Permanently Lubricated; Sleeve Type
Overload Protector	Manual Reset Type	Manual Reset Type
Shipping Weight (lbs.)	8.1	8.1
Pallet Quantity	196	196
* 36" power cord is included with a 191PC and 291PC.		



4240 E. La Palma Avenue